

WEIGHING

AD-1192 COMPACT PRINTER



A&D

AD-1192 COMPACT PRINTER

The AD-1192 is a compact, palm-sized dot-impact printer that provides users with essential functions.

Multiple Applications

Use the AD-1192 with A&D balances & scales or in data-logging applications.

Convenient

The AD-1192 is ultra compact, lightweight, low cost and operates with low power consumption. It features a paper near-end detection function.

Connectivity

RS-232C serial interface.

Features / Applications

- Compact and light weight
- Uses standard 2 1/4" paper
- High speed printing
- Paper near-end detection function
- RS-232C interface
- Low power consumption
- Wall mountable
- Balance & scale data
- Weighing slips



Power cord included

AD-1192 Specifications

Model	AD-1192	
Printing Method	Dot Matrix	
Print Direction	Uni-directional	
Character Config. (W x H)	(4+0.5) x 8	
Number of Columns	40 columns: 180 dots/line	
Print Speed	Approx. 1.8 lines/sec.	
Character Size (W x H)	1.08 x 2.4 mm	
Character Spacing	1.19 mm	
Line Pitch	3.52 mm	
Paper Feed Speed	Approx. 3.6 lines/sec.	
Paper	Single sheet, copier paper (original and copy), Total thickness: 0.13 mm or less Paper roll: 57.5 ± 0.5 (W) x 60 or 80 (Dia) mm Core ID: Ø12 ± 1 mm Core OD: Ø18 ± 1 mm	
Input Buffer	2K bytes	
Ink Ribbon	Black, Service life: approx. 250,000 characters	
Power Supply	DC 7V ± 1V (Printing) Use exclusive adapter (DC 7V 1.6A)	
Power Consumption	Printing: Approx. 7VA Stand-by: Approx. 0.5VA	
Weight	Approx. 470g	
Dimensions (W x D x H)	106 x 180 x 88 mm / 4.2 x 7.5 x 3.5 in.	
Environment	Operation	Temperature 0-40°C Humidity 35-85% RH (without condensation)
	Storage	Temperature 20-60°C Humidity 10-90% RH (without condensation)
Reliability	MCBF 1 million lines	

Specifications subject to change without notice.

Options/Accessories

- KO:1131 RS-232C Cable, 25 pin male to 25 pin male (for GF/X-K, GH, GR, GX/GF, GP, HD, HR/HRi, MC, MS/MX/MF/ML, SV/SVA, AD-4212 series)
- KO:WW9-25 RS-232C Cable, 25 pin male to 9 pin female (for BM, EJ, EKi/EWi, FCI/FCSi, FXi(WP)/FZi(WP), GH, JM)
- KO:WW25-7 RS-232C Cable, 25 pin male to 7 pin male (for FG-K, Hci, HV, HV-G, HW-G, HV-WP, HW-WP)
- AD-1192-1 Replacement Ribbon
- AD-1192-2 Replacement Power Cord
- WP:PP137 Roll Paper, 2.25ø, 5 rolls per carton



1756 Automation Parkway
San Jose, CA 95131
(800) 726-3364 or (408) 263-5333
Email: scales@andweighing.com
www.andweighing.com

© 2011 A&D Weighing



LIT: 1192 09/13